

MODEL 310 FIRE PULL STATION



OVERVIEW

The Model 310 Manual Fire Alarm Pull Station is a self contained addressable dual action lexan fire pull station with a built in transmitter. It is UL Listed 38 and complies with ADA requirements of maximum pull force as well as providing operating instructions in Braille text molded into the handle.

In addition to the supervisory features such as low battery and tamper, the Model 310 also meets the 200-second polling requirement. The Model 310 Manual Fire Alarm Pull Station utilizes FHSS (Frequency Hopping Spread Spectrum) signaling technology and provides bi-directional system communication to assure a secure and reliable communication network.

Both attractive and cost effective, the Model 310 incorporates a built in transmitter and is ideal for any application.

FEATURES

- **UL 38**
- ADA Compliant
- Highly Visible
- Key Reset
- Operates on Single 3V Lithium Battery
- Fully Supervised
- 900 MHz Band FHSS Transmission Format

* Handle latches in down position when the station has been operated with the word "Activated" displayed.



MODEL 310 FIRE PULL STATION



SPECIFICATIONS

- Battery Type: 3 Volt Lithium Duracell DL123A or Panasonic CR123A
- Battery Life: 12 Months Minimum
- Battery Replacement: Upon Low battery report and/or during annual maintenance
- Testing: Follow this manual and NFPA 72 or local requirements
- Transmission: Complies to FCC Part 15
- Test Transmission: 200 Second Supervisory Polling
- Compatibility: Commercial Wireless Systems International, LLC Model CP-3000

Height 5.49" | Width 4.25" | Depth 2.25" | Weight 10 oz.

